

Appbead Blog

- [Atom](#)

|> FLII

- [Home](#)
- [Blog](#)
- [Archives](#)
- [Featured](#)
- [Misc](#)

Fix Errors Reported in syslog for Debian 8 Jessie

May 10, 2015

After setup mail server on Debian 8 (Jessie) successfully, several errors occurred in `/var/log/syslog`.

dovecot[487]: Error: systemd listens on port 143, but it's not configured in Dovecot. Closing.

For security consideration, when configure Dovecot daemon, the IMAPS port 993 is the only one opened. Clearly, the error is caused by **systemd** socket of Dovecot.

```
$ sudo systemctl status dovecot.socket
● dovecot.socket - Dovecot IMAP/POP3 email server activation socket
  Loaded: loaded (/lib/systemd/system/dovecot.socket; enabled)
  Active: failed (Result: resources) since Sat 2015-05-09 20:18:13 CST; 1h 46min ago
  Listen: 0.0.0.0:143 (Stream)
          [::]:143 (Stream)
          0.0.0.0:993 (Stream)
          [::]:993 (Stream)
```

The solution is modify `dovecot.socket` file to indicate **systemd** the port 143 is no need to listen.

As the `systemd` prefers files in `/etc/systemd` over those in `/lib/systemd`, the correct way to modify socket/service file is copying the file `dovecot.socket` to `/etc/systemd/` firstly, and let **systemd** know it.

```
$ sudo cp /lib/systemd/system/dovecot.socket /etc/systemd/system/
$ sudo systemctl reenable dovecot.socket
Removed symlink /etc/systemd/system/sockets.target.wants/dovecot.socket.
Created symlink from /etc/systemd/system/sockets.target.wants/dovecot.socket to /etc/systemd/system/dovecot.socket.
```

Then modify the copied socket file. Here we comment out the lines include 143 port in file `dovecot.socket`

```
$ sudo sed -i 's/0.0.0.0:143/#/' /etc/systemd/system/dovecot.socket

$ sudo systemctl stop dovecot.service
$ sudo systemctl start dovecot.socket
$ sudo systemctl status dovecot.socket
● dovecot.socket - Dovecot IMAP/POP3 email server activation socket
  Loaded: loaded (/etc/systemd/system/dovecot.socket; enabled)
  Active: active (listening) since Sat 2015-05-09 22:12:05 CST; 56s ago
  Listen: 0.0.0.0:993 (Stream)
          [::]:993 (Stream)
```

The error will be gone when rebooting system, however it's not necessary to reboot at all.

fail2ban[475]: Starting authentication failure monitor: fail2banWARNING

'ignoreregex' not defined in 'Definition'. Using default one: ''

After check the conf files relative to mail server in /etc/fail2ban/filter.d/, we found the problem file is **postfix-sasl.conf**

Solution: Add a line "ignoreregex =" after failregex definition:

```
$ sudo sed -i -e '/^failregex\b/{:a;n;/^\$!ba;i\ \nignoreregex = ' -e '}' /etc/fail2ban/filter.d/postfix-sasl.conf
```

Then check if the WARNING is gone by run:

```
$ sudo service fail2ban restart  
$ sudo tail /var/log/syslog
```

console-kit-daemon GLib-CRITICAL

The error message from syslog:

```
console-kit-daemon[711]: console-kit-daemon[711]: GLib-CRITICAL: Source ID 962 was not found when attempting to remove it  
console-kit-daemon[711]: (process:8623): GLib-CRITICAL **: g_slice_set_config: assertion 'sys_page_size == 0' failed
```

ConsoleKit only manages console logins in graphical mode, so it's useless on a debian 8 based headless server^[1]. The way to remove and stop console kit:

```
$ sudo apt-get remove consolekit  
$ sudo apt-get autoremove
```

Posted by Mo Nianliang May 10, 2015 [Featured](#) [Dovecot](#), [Postfix](#), [Mail server](#), [Debian](#), [fail2ban](#)

Comments

0 Comments

Appbead Blog

5 bolt

♥ Recommend

🔗 Share

Sort by Best



Start the discussion...

Be the first to comment.

✉ Subscribe

Ⓓ Add Disqus to your site

🔒 Privacy

Recent Posts

- [Fix Errors Reported in syslog for Debian 8 Jessie](#)
- [Build Failed Gameplay3d sample spaceship on Android](#)
- ["pkg_resources.DistributionNotFound: paramiko>=1.10,<1.13"](#)
- [Export Zinnia Blog Entries to Pelican](#)
- ["No Java runtime present, requesting instal" on OS X Mountain Lion with JRE 7 u40 installed](#)

Categories

- [Featured](#)
- [misc](#)

Tags

[pelican](#), [jre](#), [XCode](#), [fail2ban](#), [Linux](#), [Mail server](#), [Live USB](#), [autocompletion](#), [GIMP](#), [java](#), [Xmodmap](#), [Dovecot](#), [Android](#), [Zinnia](#), [auto-ingest](#), [GamePlay3d](#), [Mac OS X](#), [iOS](#), [iPhone Simulator](#), [Proxy](#), [Ubuntu](#), [fab](#), [Debian](#), [Bash](#), [Qt](#), [MacPorts](#), [Postfix](#), [XQuartz](#), [mountain lion](#), [X11](#)

GitHub Repos

- Status updating...

[@appbead](#) on GitHub

Copyright © 2011–2015 Mo Nianliang — Powered by [Pelican](#)